

1968	Centerline Length	Beam	Hull Draft	Deadrise at Transom	Transom Height	Approx Weight	Fuel Capacity	Fresh Water Capacity	Max HP
17	17' - 0"	7' - 2"	7"	X	20"	1050 lbs	24 Gal.	X	115
Perdue 18	18' - 6"	7' - 9"	8"	X	20"	1250 lbs	24 Gal.	X	115
19	18' - 7"	8' - 0"	8"	X	20"	1400 lbs	32 Gal.	X	150
22	21' 9"	8' - 0"	10"	X	20"	1800 lbs	44 Gal.	X	225
25 Inboard	24' - 8"	10' - 0"	21"	X	Full	4000 lbs	104 Gal.	X	X
1969	Centerline Length	Beam	Hull Draft	Deadrise at Transom	Transom Height	Approx Weight	Fuel Capacity	Fresh Water Capacity	Max HP
17	17' - 0"	7' - 2"	7"	X	20"	1050 lbs	24 Gal.	X	115
19	18' - 7"	8' - 0"	10"	X	20"	1400 lbs	32 Gal.	X	150
22	21' - 9"	8' - 0"	10"	X	20"	1800 lbs	44 Gal.	X	225
1970	Centerline Length	Beam	Hull Draft	Deadrise at Transom	Transom Height	Approx Weight	Fuel Capacity	Fresh Water Capacity	Max HP
17	17' - 0"	7' - 2"	7"	X	20"	1050 lbs	24 Gal.	X	135
19	18' - 7"	8' - 0"	8"	X	20"	1400 lbs	32 Gal.	X	150
22	21' - 9"	8' - 0"	10"	X	20"	1800 lbs	51 Gal.	X	230
23	23' - 0"	8' - 0"	10"	X	20"	2550 lbs	70 Gal.	X	250
23 Iboard	23' - 0"	8' - 0'	22"	X	Full	3600 lbs	75 Gal.	X	X
231 Cabin I/O	23' - 0"	8' - 0'	12"	X	Full	3800 lbs	70 Gal.	X	X
232 Cabin I/O	23' - 0"	8' - 0'	12"	X	Full	3650 lbs	70 Gal.	X	X
1971	Centerline Length	Beam	Hull Draft	Deadrise at Transom	Transom Height	Approx Weight	Fuel Capacity	Fresh Water Capacity	Max HP
17	17' - 0"	7' - 2"	7"	X	20"	1050 lbs	24 Gal.	X	135
19	18' - 7"	8' - 0"	8"	X	20"	1400 lbs	32 Gal.	X	150
20	20' - 0"	8' - 0"	9"	X	20"	1600 lbs	44 Gal.	X	200
22	21' - 9"	8' - 0"	10"	X	20"	1800 lbs	51 Gal.	X	230
23 Inboard	23' - 0"	8' - 0"	22"	X	Full	3600 lbs	75 Gal.	X	X
231 Cabin I/O	23' - 0"	8' - 0"	12"	X	Full	3800 lbs	70 Gal.	X	X
232 Cabin I/O	23' - 0"	8' - 0"	12"	X	Full	3650 lbs	70 Gal.	X	X
1972	Centerline Length	Beam	Hull Draft	Deadrise at Transom	Transom Height	Approx Weight	Fuel Capacity	Fresh Water Capacity	Max HP
17 Standard	17' - 0"	7' - 2"	7"	X	20"	1050 lbs	24 Gal.	X	135
17 Angler	17' - 0"	7' - 2"	7"	X	20"	1050 lbs	24 Gal.	X	135
19	18' - 7"	7' - 2"	8"	X	20"	1400 lbs	32 Gal.	X	150
20	20' - 0"	8' - 0"	9"	X	20"	1600 lbs	44 Gal.	X	200

22	21' - 9"	8' - 0"	10"	X	20"	1800 lbs	51 Gal.	X	230
23	23' - 0"	8' - 0"	10"	X	20"	2550 lbs	70 Gal.	X	250
23 Cabin I/O	23' - 0"	8' - 0"	12"	X	Full	3800 lbs	70 Gal.	X	X
23 Open I/O	23' - 0"	8' - 0"	12"	X	Full	36560 lbs	70 Gal.	v	X
1973	Centerline Length	Beam	Hull Draft	Deadrise at Transom	Transom Height	Approx Weight	Fuel Capacity	Fresh Water Capacity	Max HP
17 Standard	17' - 0"	7' - 2"	7"	12°	20"	1050 lbs	24 Gal.	X	135
17 Angler	17' - 0"	7' - 2"	7"	12°	20"	1050 lbs	24 Gal.	X	135
19	18' - 7"	7' - 2"	8"	X	20"	1400 lbs	32 Gal.	X	150
20	20' - 0"	8' - 0"	9"	19°	20"	1600 lbs	44 Gal.	X	200
22	21' - 9"	8' - 0"	10"	X	20"	1800 lbs	51 Gal.	X	230
23	23' - 0"	8' - 0"	10"	X	20"	2550 lbs	70 Gal.	X	250
23 Cabin I/O	23' - 0"	8' - 0"	12"	X	Full	3800 lbs	70 Gal.	X	X
23 Open I/O	23' - 0"	8' - 0"	12"	X	Full	3650 lbs	70 Gal.	X	X
1974	Centerline Length	Beam	Hull Draft	Deadrise at Transom	Transom Height	Approx Weight	Fuel Capacity	Fresh Water Capacity	Max HP
15	15' - 0"	6' - 2"	6"	X	20"	850 lbs	X	X	70
17 Standard	17' - 0"	7' - 2"	7"	X	20"	1050 lbs	24 Gal.	X	135
17 Angler	17' - 0"	7' - 2"	7"	X	20"	1050 lbs	24 Gal.	X	135
19B	18' - 7"	8' - 0"	8"	X	20"	1400 lbs	32 Gal.	X	150
20	20' - 0"	8' - 0"	9"	X	20"	1600 lbs	44 Gal.	X	200
22B	21' - 9"	8' - 0"	10"	X	20"	1800 lbs	51 Gal.	X	230
23	23' - 0"	8' - 0"	10"	X	20"	2550 lbs	70 Gal.	X	250
23 Cabin I/O	23' - 0"	8' - 0"	12"	X	Full	3800 lbs	70 Gal.	X	X
23 Open I/O	23' - 0"	8' - 0"	12"	X	Full	3650 lbs	70 Gal.	X	X
1975	Centerline Length	Beam	Hull Draft	Deadrise at Transom	Transom Height	Approx Weight	Fuel Capacity	Fresh Water Capacity	Max HP
15	15' - 0"	6' - 2"	6"	X	20"	850 lbs	X	X	70
17 Standard	17' - 0"	7' - 2"	7"	X	20"	1050 lbs	24 Gal.	X	135
17 Angler	17' - 0"	7' - 2"	7"	X	20"	1050 lbs	24 Gal.	X	135
19B	18' - 7"	8' - 0"	8"	X	20"	1400 lbs	32 Gal.	X	150
20	20' - 0"	8' - 0"	9"	X	20"	1600 lbs	44 Gal.	X	200
22B	21' - 9"	8' - 0"	10"	X	20"	1800 lbs	51 Gal.	X	230
23	23' - 0"	8' - 0"	10"	X	20"	2550 lbs	70 Gal.	X	250
23 Cabin I/O	23' - 0"	8' - 0"	12"	X	Full	3800 lbs	70 Gal.	X	X

23 Open I/O	23'-0"	8'- 0"	12"	X	Full	3650 lbs	70 Gal.	X	X
23 Inboard	23'-0"	8'- 0"	22"	X	Full	3600 lbs	74 Gal.	X	260
26 Inboard	26'-0"	9'- 6"	22"	X	Full	6500 lbs	110 Gal.	X	X
1976	Centerline Length	Beam	Hull Draft	Deadrise at Transom	Transom Height	Approx Weight	Fuel Capacity	Fresh Water Capacity	Max HP
171 Classic	17'- 0"	7'- 2"	7"	X	20"	1400 lbs	24 Gal.	X	135
171 Angler	17'-0"	7'-2"	7"	X	20"	1200 lbs	24 Gal.	X	135
19B	18'-7"	8'- 0"	8"	X	20"	1525 lbs	32 Gal.	X	150
20	20'-0"	8'- 0"	9"	X	20"	1775 lbs	44 Gal.	X	200
22B	21'-9"	8'- 0"	10"	X	20"	1950 lbs	51 Gal.	X	230
23	23'-0"	8'- 0"	10"	X	25"	2500 lbs	70 Gal.	X	250
23 Cabin I/O	23'-0"	8'- 0"	12"	X	Full	3650 lbs	70 Gal.	X	X
23 OpenI/O	23'-0"	8'- 0"	12"	X	Full	3650 lbs	70 Gal.	X	X
23 Inboard	23'-0"	8'- 0"	22"	X	Full	3600 lbs	74 Gal.	X	260
25	25'-7"	8'- 0"	14"	X	25"	2900 lbs	120 Gal.	X	300
26 Inboard	26'-0"	9'- 6"	22"	X	Full	6500 lbs	110 Gal.	X	X
1977	Centerline Length	Beam	Hull Draft	Deadrise at Transom	Transom Height	Approx Weight	Fuel Capacity	Fresh Water Capacity	Max HP
15	15'- 0"	6'- 2"	6"	X	20"	875 lbs	X	X	70
17 Standard	17'-0"	7'-2"	7"	X	20"	1400 lbs	24 Gal.	X	135
17 Angler	17'-0"	7'- 2"	7"	X	20"	1200 lbs	24 Gal.	X	135
19B	18'-7"	8'- 0"	8"	X	20"	1525 lbs	32 Gal.	X	150
20	20'-0"	8'- 0"	9"	X	20"	1775 lbs	44 Gal.	X	200
21	21'-0"	8'- 0"	12"	X	25"	2100 lbs	86 Gal.	X	200
22B	21'-9"	8'- 0"	10"	X	20"	2000 lbs	51 Gal.	X	230
23	23'-0"	8'- 0"	10"	X	25"	2500 lbs	86 Gal.	X	250
23 Inboard	23'-0"	8'- 0"	24"	X	Full	3800 lbs	80 Gal.	X	260
25	25'-7"	8'- 0"	14"	X	25"	2700 lbs	86 Gal.	X	300
26 Inboard	26'-0"	9'- 6"	22"	X	Full	6500 lbs	110 Gal.	X	X
1978	Centerline Length	Beam	Hull Draft	Deadrise at Transom	Transom Height	Approx Weight	Fuel Capacity	Fresh Water Capacity	Max HP
17 Standard	17'- 0"	7'- 2"	7"	X	20"	1400 lbs	24 Gal.	X	135
17 Angler	17'-0"	7'-2"	7"	X	20"	1200 lbs	24 Gal.	X	135
19B	18'-7"	8'- 0"	8"	X	20"	1525 lbs	32 Gal.	X	150
20	20'-0"	8'- 0"	9"	X	20"	1775 lbs	44 Gal.	X	200

21	21'-0"	8'- 0"	12"	X	25"	2100 lbs	86 Gal.	X	230
23	23'-0"	8'- 0"	10"	X	25"	2500 lbs	86 Gal.	X	250
23 Inboard	23'-0"	8'- 0"	24"	X	Full	3800 lbs	80 Gal.	X	260
25	25'-7"	8'- 0"	14"	X	25"	2700 lbs	86 Gal.	X	300

1979	Centerline Length	Beam	Hull Draft	Deadrise at Transom	Transom Height	Approx Weight	Fuel Capacity	Fresh Water Capacity	Max HP
17 Standard	17'- 0"	7'- 2"	7"	X	20"	1400 lbs	24 Gal.	X	135
17 Angler	17'-0"	7'-2"	7"	X	20"	1200 lbs	24 Gal.	X	135
19B	18'-7"	8'- 0"	8"	X	20"	1525 lbs	32 Gal.	X	150
20	20'-0"	8'- 0"	9"	X	20"	1775 lbs	44 Gal.	X	200
21	21'-0"	8'- 0"	12"	X	25"	2100 lbs	86 Gal.	X	230
23	23'-0"	8'- 0"	10"	X	25"	2500 lbs	86 Gal.	X	250
23 Inboard	23'-0"	8'- 0"	24"	X	Full	3800 lbs	80 Gal.	X	260
25	25'-7"	8'- 0"	14"	X	25"	2700 lbs	86 Gal.	X	300

1980	Centerline Length	Beam	Hull Draft	Deadrise at Transom	Transom Height	Approx Weight	Fuel Capacity	Fresh Water Capacity	Max HP
17 Standard	17' - 0"	7' - 2"	7"	12°	20"	1400 lbs	24 Gal.	X	135
17 Angler	17' - 0"	7' - 2"	7"	12°	20"	1200 lbs	24 Gal.	X	135
18	18' - 2"	6' - 7"	6"	X	20"	1150 lbs	30 Gal.	X	140
20B	20' - 0"	8' - 0"	9"	19°	20"	1775 lbs	60 Gal.	X	200
21	21' - 0"	8' - 0"	12"	19°	25"	2100 lbs	86 Gal.	X	230
224	22' - 7"	8' - 0"	14"	19°	25"	2200 lbs	112 Gal.	X	250
228 Cuddy	22' - 7"	8' - 0"	14"	19°	25"	2300 lbs	122 Gal.	X	250
235	23' - 0"	8' - 0"	10"	19°	25"/30"	2500 lbs	122 Gal.	X	250
236 Inboard	23' - 0"	8' - 0"	24"	16°	Full	3800 lbs	80 Gal.	X	260
238 Walk Around	23' - 0"	8' - 6"	14"	X	25"	2500 lbs	121 Gal.	X	250
25	25' - 7"	8' - 0"	14"	23°	25"	2800 lbs	151 Gal.	X	300
258 Cuddy	25' - 6"	8' - 0"	18"	23°	25"	3200 lbs	151 Gal.	X	300

1981	Centerline Length	Beam	Hull Draft	Deadrise at Transom	Transom Height	Approx Weight	Fuel Capacity	Fresh Water Capacity	Max HP
17 Standard	17'- 0"	7'- 2"	7"	12°	20"	1400 lbs	35 Gal.	X	135
17 Angler	17'-0"	7'-2"	7"	12°	20"	1200 lbs	35 Gal.	X	135
20B	20'-0"	8'- 0"	9"	19°	20"	1775 lbs	60 Gal.	X	200
21	21'-3"	8'- 0"	12"	19°	25"	2100 lbs	86 Gal.	X	230
224	22'-7"	8'- 0"	14"	19°	25"	2200 lbs	112 Gal.	X	250

228 Cuddy	22'-7"	8'- 0"	14"	19°	25"	2300 lbs	122 Gal.	X	250
235	23'-0"	8'- 0"	10"	19°	25"/30"	2500 lbs	122 Gal.	X	250
236 Inboard	23'-0"	8'- 0"	24"	16°	Full	3800 lbs	80 Gal.	X	260
238 Walk Around	23'-0"	8'- 6"	14"	X	25"	2500 lbs	121 Gal.	X	250
25	25'-7"	8'- 0"	14"	23°	25"	2800 lbs	151 Gal.	X	300
258 Cuddy	25'-6"	8'- 0"	18"	23°	25"	3200 lbs	151 Gal.	X	300

1982	Centerline Length	Beam	Hull Draft	Deadrise at Transom	Transom Height	Approx Weight	Fuel Capacity	Fresh Water Capacity	Max HP
17 Standard	17'- 0"	7'- 2"	7"	12°	20"	1400 lbs	35 Gal.	X	135
17 Angler	17'-0"	7'-2"	7"	12°	20"	1200 lbs	35 Gal.	X	135
20B	20'-0"	8'- 0"	9"	19°	20"	1775 lbs	60 Gal.	X	200
21	21'-3"	8'- 0"	12"	19°	25"	2100 lbs	86 Gal.	X	230
224	22'-7"	8'- 0"	14"	19°	25"	2200 lbs	112 Gal.	X	250
228 Cuddy	22'-7"	8'- 0"	14"	19°	25"	2300 lbs	122 Gal.	X	250
235	23'-0"	8'- 0"	10"	19°	25"/30"	2500 lbs	122 Gal.	X	250
236 Inboard	23'-0"	8'- 0"	24"	16°	Full	3800 lbs	80 Gal.	X	260
238 Walk Around	23'-0"	8'- 6"	14"	X	25"	2500 lbs	121 Gal.	X	250
25	25'-7"	8'- 0"	14"	23°	25"	2800 lbs	151 Gal.	X	300
258 Cuddy	25'-6"	8'- 0"	18"	23°	25"	3200 lbs	151 Gal.	X	300

1983	Centerline Length	Beam	Hull Draft	Deadrise at Transom	Transom Height	Approx Weight	Fuel Capacity	Fresh Water Capacity	Max HP
17 Standard	17'- 0"	7'- 2"	7"	12°	20"	1400 lbs	35 Gal.	X	135
17 Angler	17'-0"	7'-2"	7"	12°	20"	1200 lbs	35 Gal.	X	135
18	18'-2"	6'-7"	6"	X	20"	1150 lbs	30 Gal.	X	140
20B	20'-0"	8'- 0"	9"	19°	20"	1775 lbs	60 Gal.	X	200
21	21'-3"	8'- 0"	12"	19°	25"	2100 lbs	86 Gal.	X	230
224	22'-7"	8'- 0"	14"	19°	25"	2200 lbs	112 Gal.	X	250
228 Cuddy	22'-7"	8'- 0"	14"	19°	25"	2300 lbs	122 Gal.	X	250
235	23'-0"	8'- 0"	10"	19°	25"/30"	2500 lbs	122 Gal.	X	250
236 Inboard	23'-0"	8'- 0"	24"	16°	Full	3800 lbs	80 Gal.	X	260
238 Walkaround	23'-0"	8'- 6"	14"	X	25"	2500 lbs	121 Gal.	X	250
25	25'-7"	8'- 0"	14"	23°	25"	2800 lbs	151 Gal.	X	300
258 Cuddy	25'-6"	8'- 0"	18"	23°	25"	3200 lbs	151 Gal.	X	300

1984	Centerline Length	Beam	Hull Draft	Deadrise at Transom	Transom Height	Approx Weight	Fuel Capacity	Fresh Water Capacity	Max HP
-------------	-------------------	------	------------	---------------------	----------------	---------------	---------------	----------------------	--------

172 Standard	17'- 0"	7'- 2"	7"	12°	20"	1400 lbs	35 Gal.	X	135
171 Angler	17'-0"	7'-2"	7"	12°	20"	1200 lbs	35 Gal.	X	135
20C	20'-0"	8'-0"	9"	19°	20"	1775 lbs	60 Gal.	X	200
21B	21'-7"	8'- 0"	12"	19°	25"	2100 lbs	86 Gal.	X	235
224	22'-7"	8'- 0"	14"	19°	25"	2200 lbs	112 Gal.	X	240
228 Cuddy	22'-7"	8'- 0"	13"	19°	25"	2300 lbs	123 Gal.	X	240
235	23'-0"	8'- 0"	12"	19°	25"/30"	2500 lbs	122 Gal.	X	250
236 Inboard	23'-0"	8'- 0"	24"	16°	Full	3800 lbs	80 Gal.	X	260
238 WalkAround	23'-0"	8'- 6"	14"	X	25"	2500 lbs	121 Gal.	X	250
254	25'-7"	8'- 0"	14"	23°	25"/30"	2800 lbs	151 Gal.	X	370
258 Cuddy	25'-7"	8'- 0"	18"	23°	25"/30"	3200 lbs	151 Gal.	X	370
284	28'-5"	9'-10"	24"	X	25"T	6000 lbs	300 Gal.	X	600
286	28'-5"	9'- 10"	30"	13°	Full	8000 lbs	230 Gal.	X	X

1985	Centerline Length	Beam	Hull Draft	Deadrise at Transom	Transom Height	Approx Weight	Fuel Capacity	Fresh Water Capacity	Max HP
171 Standard	17'- 0"	7'- 2"	7"	12 °	20"	1400 lbs	35 Gal.	X	135
171 Angler	17'-0"	7'-2"	7"	12 °	20"	1200 lbs	35 Gal.	X	135
20C	20'-0"	8'-0"	9"	19 °	20"	1775 lbs	60 Gal.	X	200
21B	21'-7"	8'- 0"	12"	19 °	25"	2100 lbs	86 Gal.	X	235
224	22'-7"	8'- 0"	14"	19 °	25"	2200 lbs	112 Gal.	X	240
228 Cuddy	22'-7"	8'- 0"	13"	19 °	25"	2300 lbs	123 Gal.	X	240
235	23'-0"	8'- 0"	12"	19 °	25"/30"	2500 lbs	122 Gal.	X	250
236 Inboard	23'-0"	8'- 0"	24"	16 °	Full	3800 lbs	80 Gal.	X	260
238 WalkAround	23'-0"	8'- 6"	14"	X	25"	2500 lbs	121 Gal.	X	250
254	25'-7"	8'- 0"	14"	23 °	25"/30"	2800 lbs	151 Gal.	X	370
258 Cuddy	25'-7"	8'- 0"	18"	23 °	25"/30"	3200 lbs	151 Gal.	X	370
284	28'-5"	9'-10"	24"	X	25"T	6000 lbs	300 Gal.	X	600
286	28'-5"	9'- 10"	30"	13 °	Full	8000 lbs	230 Gal.	X	X

1986	Centerline Length	Beam	Hull Draft	Deadrise at Transom	Transom Height	Approx Weight	Fuel Capacity	Fresh Water Capacity	Max HP
171 Standard	17'- 0"	7'- 2"	7"	12°	20"	1400 lbs	35 Gal.	X	135
171 Angler	17'-0"	7'-2"	7"	12°	20"	1200 lbs	35 Gal.	X	135
20C	20'-0"	8'-0"	9"	19°	20"	1775 lbs	60 Gal.	X	200
21B	21'-7"	8'- 0"	12"	19°	25"	2100 lbs	86 Gal.	X	235
224	22'-7"	8'- 0"	14"	19°	25"	2200 lbs	112 Gal.	X	240

228 Cuddy	22'-7"	8'- 0"	13"	19°	25"	2300 lbs	123 Gal.	X	240
231	23'-2"	8'- 0"	12"	19°	25"/30"	2880 lbs	160 Gal.	X	250
236 Inboard	23'-0"	8'- 0"	24"	16°	Full	3800 lbs	80 Gal.	X	260
248 WalkAround	24'-7"	8'- 6"	12"	X	25"/28.5"	3000 lbs	150 Gal.	X	280
254	25'-7"	8'- 0"	14"	23°	25"/30"	2800 lbs	151 Gal.	X	370
258 Cuddy	25'-7"	8'- 0"	18"	23°	25"/30"	3200 lbs	151 Gal.	X	370
261	26'-4"	8'-6"	16"	23°	25"/30"	3600 lbs	200 Gal.	X	400
284/285	28'-5"	9'- 10"	24"	X	25"T	6000 lbs	300 Gal.	X	600
286	28'-5"	9'-10"	30"	13°	Full	8000 lbs	230 Gal.	X	X

1987	Centerline Length	Beam	Hull Draft	Deadrise at Transom	Transom Height	Approx Weight	Fuel Capacity	Fresh Water Capacity	Max HP
172 Standard	17'- 0"	7'- 2"	7"	12°	20"	1400 lbs	35 Gal.	X	135
171 Angler	17'-0"	7'-2"	7"	12°	20"	1200 lbs	35 Gal.	X	135
20C	20'-0"	8'-0"	9"	19°	20"	1775 lbs	60 Gal.	X	200
21B	21'-7"	8'- 0"	12"	19°	25"	2100 lbs	86 Gal.	X	235
224	22'-7"	8'- 0"	14"	19°	25"	2200 lbs	112 Gal.	X	240
228 Cuddy	22'-7"	8'- 0"	13"	19°	25"	2300 lbs	123 Gal.	X	240
231	23'-2"	8'- 0"	12"	19°	25"/30"	2880 lbs	160 Gal.	X	250
236 Inboard	23'-0"	8'- 0"	24"	16°	Full	3800 lbs	80 Gal.	X	260
248 WalkAround	24'-7"	8'- 6"	12"	X	25"/28.5"	3000 lbs	150 Gal.	X	280
254	25'-7"	8'- 0"	14"	23°	25"/30"	2800 lbs	151 Gal.	X	370
258 Cuddy	25'-7"	8'- 0"	18"	23°	25"/30"	3200 lbs	151 Gal.	X	370
261	26'-4"	8'-6"	16"	23°	25"/30"	3600 lbs	200 Gal.	X	400
284/285	28'-5"	9'- 10"	24"	X	25"T	6000 lbs	300 Gal.	X	600
286	28'-5"	9'-10"	30"	13°	Full	8000 lbs	230 Gal.	X	X

1988	Centerline Length	Beam	Hull Draft	Deadrise at Transom	Transom Height	Approx Weight	Fuel Capacity	Fresh Water Capacity	Max HP
172 Standard	17'- 0"	7'- 2"	7"	12°	20"	1400 lbs	35 Gal.	X	135
171 Angler	17'-0"	7'-2"	7"	12°	20"	1200 lbs	35 Gal.	X	135
20C	20'-0"	8'-0"	9"	19°	20"	1775 lbs	60 Gal.	X	200
21B	21'-7"	8'- 0"	12"	19°	25"	2100 lbs	86 Gal.	X	235
224	22'-7"	8'- 0"	14"	19°	25"	2200 lbs	112 Gal.	X	240
228 Cuddy	22'-7"	8'- 0"	13"	19°	25"	2300 lbs	123 Gal.	X	240
231	23'-2"	8'- 0"	12"	19°	25"/30"	2880 lbs	160 Gal.	X	250
236 Inboard	23'-0"	8'- 0"	24"	16°	Full	3800 lbs	80 Gal.	X	260

248 WalkAround	24'-7"	8'- 6"	12"	X	25"/28.5"	3000 lbs	150 Gal.	X	280
254	25'-7"	8'- 0"	14"	23°	25"/30"	2800 lbs	151 Gal.	X	370
258 Cuddy	25'-7"	8'- 0"	18"	23°	25"/30"	3200 lbs	151 Gal.	X	370
261	26'-4"	8'-6"	16"	23°	25"/30"	3600 lbs	200 Gal.	X	400
284/285	28'-5"	9'- 10"	24"	X	25"T	6000 lbs	300 Gal.	X	600
286	28'-5"	9'-10"	30"	13°	Full	8000 lbs	230 Gal.	X	X
1989	Centerline Length	Beam	Hull Draft	Deadrise at Transom	Transom Height	Approx Weight	Fuel Capacity	Fresh Water Capacity	Max HP
171 Classic	17'- 0"	7'- 2"	7"	12°	20"	1400 lbs	35 Gal.	X	135
171 Angler	17'-0"	7'-2"	7"	12°	20"	1200 lbs	35 Gal.	X	135
191 Classic	19'-0"	8'-0"	9"	19°	25"	1900 lbs	60 Gal.	X	150
201	20'-3"	8'- 0"	9"	19°	25"	2150 lbs	60 Gal.	X	200
210 Walk Arounc	21'-3"	8'- 0"	13"	20°	25"	2500 lbs	110 Gal.	X	230
211	21'-8"	8'- 0"	13"	19°	25"	2400 lbs	86 Gal.	X	235
220 Cuddy	22'-7"	8'- 0"	13"	19°	25"	2500 lbs	110 Gal.	X	240
221	22'-8"	8'- 0"	13"	19°	25"	2480 lbs	110 Gal.	X	250
230 WalkAround	23'-0"	8'- 0"	14"	17°	20"/25"	2800 lbs	120 Gal.	X	250
231	23'-2"	8'- 0"	13"	19°	25"/30"	2880 lbs	150 Gal.	X	250
236 Inboard	23'-0"	8'- 0"	24"	16°	Full	3800 lbs	80 Gal.	X	260
240 Walk Arounc	24'-6"	8'-6"	14"	23°	Full	3600 lbs	150 Gal.	X	280
241	24'-4"	8'- 6"	16"	23°	25"/30"	3400 lbs	180 Gal.	X	400
250 Cuddy	25'-7"	8'-0"	18"	23°	25"/30"	3200 lbs	151 Gal.	X	370
251	25'-7"	8'- 0"	14"	23°	25"/30"	3200 lbs	151 Gal.	X	370
260	26'-0"	8'-6"	14"	23°	30"	4750 lbs	200 Gal.	X	400
261	26'-0"	8'- 6"	16"	23°	25"/30"	3600 lbs	200 Gal.	X	400
281/285	28'-5"	9'-10"	24"	X	30"	6000 lbs	300 Gal.	X	600
286	28'-5"	9'- 10"	30"	13°	Full	8000 lbs	230 Gal.	X	X
1990	Centerline Length	Beam	Hull Draft	Deadrise at Transom	Transom Height	Approx Weight	Fuel Capacity	Fresh Water Capacity	Max HP
171 Classic	17'- 0"	7'- 2"	7"	12°	20"	1400 lbs	35 Gal.	X	135
171 Angler	17'-0"	7'-2"	7"	12°	20"	1200 lbs	35 Gal.	X	135
191 Classic	19'-0"	8'-0"	9"	12°	25"	1900 lbs	60 Gal.	X	150
201	20'-3"	8'- 0"	9"	19°	25"	2150 lbs	60 Gal.	X	200
210 Walk Arounc	21'-3"	8'- 0"	13"	20°	25"	2500 lbs	110 Gal.	X	230
211	21'-8"	8'- 0"	13"	19°	25"	2400 lbs	86 Gal.	X	235

221	22'-8"	8'- 0"	13"	19°	25"	2480 lbs	110 Gal.	X	250
230 WalkAround	23'-0"	8'- 0"	13"	17°	20"/25"	2800 lbs	120 Gal.	X	250
230B WalkAroun	23'-0"	8'- 0"	14"	17°	Full	2800 lbs	120 Gal.	X	250
231	23'-2"	8'- 0"	13"	19°	25"/30"	2880 lbs	150 Gal.	X	250
236 Inboard	23'-0"	8'- 0"	24"	16°	Full	6800 lbs	80 Gal.	X	260
241	24'-4"	8'-6"	16"	23°	25"/30"	3400 lbs	180 Gal.	X	400
250 WalkAround	25'-4"	8'- 6"	18"	23°	30"	3500 lbs	151 Gal.	X	400
250B WalkAroun	25'-4"	8'-6"	18"	23°	Full	3500 lbs	151 Gal.	25 Gal.	400
251	25'-7"	8'- 0"	14"	23°	25"/30"	3200 lbs	151 Gal.	X	370
260	26'-0"	8'-6"	14"	23°	30"	4750 lbs	200 Gal.	X	400
260B	26'-0"	8'- 6"	14"	23°	Full	4750 lbs	200 Gal.	25 Gal.	400
261	26'-0"	8'-6"	16"	23°	25"/30"	3600 lbs	200 Gal.	X	400
281/285	28'-5"	9'- 10"	24"	X	30"	6000 lbs	300 Gal.	X	600
286	28'-5"	9'-10"	30"	13°	Full	8000 lbs	230 Gal.	20 Gal.	X

1991	Centerline Length	Beam	Hull Draft	Deadrise at Transom	Transom Height	Approx Weight	Fuel Capacity	Fresh Water Capacity	Max HP
171 Classic	17'- 3"	7'- 2"	7"	12°	20"	1250 lbs	35 Gal.	X	135
171 Angler	17'-3"	7'-2"	7"	12°	20"/25"	1250 lbs	35 Gal.	X	135
191 Classic	19'-0"	8'-0"	9"	12°	25"	1900 lbs	60 Gal.	X	150
201	20'-3"	8'- 0"	9"	19°	25"	2150 lbs	60 Gal.	X	200
210 Walk Arounc	21'-3"	8'- 0"	13"	20°	25"	2620 lbs	110 Gal.	X	230
211	21'-8"	8'- 0"	13"	19°	25"	2400 lbs	86 Gal.	X	235
221	22'-8"	8'- 0"	13"	19°	25"	2480 lbs	110 Gal.	X	250
230 WalkAround	23'-0"	8'- 0"	14"	17°	20"/25"	2800 lbs	120 Gal.	X	250
230B WalkAroun	23'-0"	8'- 0"	14"	17°	Full	2800 lbs	120 Gal.	X	250
231	23'-2"	8'- 0"	13"	19°	25"/30"	2880 lbs	150 Gal.	X	250
236 Inboard	23'-0"	8'- 0"	24"	16°	Full	6800 lbs	80 Gal.	X	260
241	24'-4"	8'-6"	16"	23°	25"/30"	3400 lbs	180 Gal.	X	400
250 WalkAround	25'-4"	8'- 6"	18"	23°	30"	3500 lbs	151 Gal.	X	400
250B WalkAroun	25'-4"	8'-6"	18"	23°	Full	3500 lbs	151 Gal.	25 Gal.	400
251	25'-7"	8'- 0"	14"	23°	25"/30"	3200 lbs	151 Gal.	X	370
260	26'-0"	8'-6"	14"	23°	30"	4750 lbs	200 Gal.	25 Gal.	400
260B	26'-0"	8'- 6"	14"	23°	Full	4750 lbs	200 Gal.	25 Gal.	400
261	26'-0"	8'-6"	16"	23°	25"/30"	3600 lbs	200 Gal.	X	400
261B	26'-4"	8'- 6"	16"	23°	Full	3900 lbs	200 Gal.	X	400

281/285	28'-5"	9'-10"	24"	X	30"	6000 lbs	300 Gal.	X	600
286	28'-5"	9'- 10"	30"	13°	Full	8000 lbs	230 Gal.	20 Gal.	X

1992	Centerline Length	Beam	Hull Draft	Deadrise at Transom	Transom Height	Approx Weight	Fuel Capacity	Fresh Water Capacity	Max HP
171 Classic	17'- 3"	7'- 2"	9"	12°	20"	1250 lbs	35 Gal.	X	135
171 Angler	17'-3"	7'-2"	9"	12°	20"/25"	1250 lbs	35 Gal.	X	135
181 Flats	17'-10"	8'-0"	7"	12°	20"	995 lbs	50 Gal.	X	150
191 Classic	19'-0"	8'- 0"	9"	12°	25"	1900 lbs	60 Gal.	X	150
201	20'-3"	8'- 0"	9"	19°	25"	2150 lbs	60 Gal.	X	200
210 WalkAround	21'-9"	8'- 0"	13"	20°	25"	2700 lbs	98 Gal.	X	230
211 Classic	21'-10"	8'- 0"	13"	19°	25"	2200 lbs	110 Gal.	X	250
215 Dual	21'-10"	8'- 0"	13"	19°	25"	2300 lbs	110 Gal.	X	250
221	22'-8"	8'- 0"	13"	19°	25"/30"	2600 lbs	150 Gal.	X	280
221B	22'-8"	8'- 0"	13"	19°	Full	2600 lbs	150 Gal.	X	280
230 WalkAround	23'-0"	8'- 0"	14"	17°	25"	3100 lbs	120 Gal.	X	250
230B WalkAroun	23'-0"	8'-0"	14"	17°	Full	3100 lbs	120 Gal.	X	260
236 Inboard	23'-0"	8'- 0"	24"	16°	Full	3800 lbs	80 Gal.	X	260
241	24'-4"	8'-6"	16"	23°	25"/30"	3800 lbs	185 Gal.	X	400
250 WalkAround	25'-8"	8'- 6"	18"	23°	30"	4000 lbs	181 Gal.	X	400
250B WalkAroun	25'-8"	8'-6"	18"	23°	Full	4000 lbs	181 Gal.	25 Gal.	400
251	25'-7"	8'- 0"	14"	23°	25"/30"	3400 lbs	151 Gal.	X	370
261	26'-0"	8'-6"	16"	23°	25"/30"	3900 lbs	200 Gal.	X	400
261B	26'-4"	8'- 6"	16"	23°	Full	3900 lbs	200 Gal.	X	400
270B WalkAroun	27'-8"	8'-6"	17.5"	23°	Full	4750 lbs	200 Gal.	25 Gal.	400
286	28'-5"	9'- 10"	30"	13°	Full	8000 lbs	213 Gal.	20 Gal.	X

1993	Centerline Length	Beam	Hull Draft	Deadrise at Transom	Transom Height	Approx Weight	Fuel Capacity	Fresh Water Capacity	Max HP
151 Flats	15'- 5"	6'- 6"	6"	12°	20"	700 lbs	25 Gal.	X	90
161 Flats	16'-9"	7'-3"	6"	12°	20"	850 lbs	35 Gal.	X	130
171 Classic	17'- 3"	7'- 2"	9"	12°	20"	1250 lbs	35 Gal.	X	135
171 Angler	17'-3"	7'-2"	9"	12°	20"/25"	1250 lbs	35 Gal.	X	135
181 Flats	17'-10"	8'-0"	7"	12°	20"	995 lbs	50 Gal.	X	150
191 Classic	19'-0"	8'- 0"	9"	12°	25"	1900 lbs	60 Gal.	X	150
211 Classic	21'-10"	8'- 0"	13"	19°	25"	2200 lbs	110 Gal.	X	250
213 Classic	21'-9"	8'- 0"	13"	20°	25"	2700 lbs	98 Gal.	X	230

215 Dual	21'-10"	8'- 0"	13"	19°	25"	2400 lbs	110 Gal.	X	250
221	22'-8"	8'- 0"	13"	19°	25"/30"	2600 lbs	150 Gal.	X	280
221B	22'-8"	8'- 0"	13"	19°	Full	2600 lbs	150 Gal.	X	250
233 WalkAround	24'-9"	8'- 6"	16"	23°	Full	3800 lbs	165 Gal.	25 Gal.	350
236 Inboard	23'-0"	8'- 0"	24"	16°	Full	3800 lbs	80 Gal.	X	260
241	24'-4"	8'-6"	16"	23°	25"/30"	3800 lbs	185 Gal.	X	400
251	25'-7"	8'- 0"	14"	23°	25"/30"	3400 lbs	151 Gal.	X	370
253B	25'-8"	8'-6"	16"	23°	Full	4000 lbs	181 Gal.	25 Gal.	400
261	26'-0"	8'- 6"	16"	23°	25"/30"	3900 lbs	200 Gal.	X	400
261B	26'-4"	8'-6"	16"	23°	Full	3900 lbs	200 Gal.	X	400
263 WalkAround	28'-7"	9'- 6"	19"	23°	Full	5000 lbs	240 Gal.	40 Gal.	550
273B WalkAroun	27'-8"	8'-6"	17.5"	23°	Full	4750 lbs	200 Gal.	25 Gal.	400
286	28'-5"	9'- 10"	30"	13°	Full	8000 lbs	230 Gal.	20 Gal.	X
290 Sportsfish	28'-3"	10'-0"	23"	13°	Full	7500 lbs	300 Gal.	40 Gal.	600
295 Sportfish	31'-3"	10'- 0"	21"	13°	Full	6800 lbs	300 Gal.	40 Gal.	600

1994	Centerline Length	Beam	Hull Draft	Deadrise at Transom	Transom Height	Approx Weight	Fuel Capacity	Fresh Water Capacity	Max HP
161 Flats	16'-9"	7'-3"	6"	12°	20"	850 lbs	35 Gal.	X	130
171 Classic	17'- 3"	7'- 2"	9"	12°	20"	1250 lbs	35 Gal.	X	135
171 Angler	17'-3"	7'-2"	9"	12°	20"/25"	1250 lbs	35 Gal.	X	135
181 Flats	17'-10"	8'-0"	7"	12°	20"	995 lbs	50 Gal.	X	150
191 Classic	19'-0"	8'- 0"	9"	12°	25"	1900 lbs	60 Gal.	X	150
195 Dual	19'-10"	8'- 0"	13"	19°	25"	2000 lbs	86 Gal.	X	200
201	20'-4"	8'- 0"	11"	19°	25"	2150 lbs	100 Gal.	X	200
211 Classic	21'-10"	8'- 0"	13"	19°	25"	2200 lbs	110 Gal.	X	250
213 Classic	21'-9"	8'- 0"	13"	20°	Full	2700 lbs	98 Gal.	X	230
215 Dual	21'-10"	8'- 0"	13"	19°	25"	2400 lbs	110 Gal.	X	250
221	22'-8"	8'- 0"	13"	19°	25"/30"	2600 lbs	150 Gal.	X	280
221B	22'-8"	8'- 0"	13"	19°	Full	2600 lbs	150 Gal.	X	250
233 WalkAround	24'-9"	8'- 6"	16"	23°	Full	3800 lbs	165 Gal.	25 Gal.	350
236 Inboard	23'-0"	8'- 0"	24"	16°	Full	3800 lbs	80 Gal.	X	260
241	24'-4"	8'-6"	16"	23°	25"/30"	3800 lbs	185 Gal.	X	400
241B	26'-2"	8'- 6"	16"	23°	Full	3800 lbs	150 Gal.	X	400
243 WalkAround	26'-2"	8'-6"	16"	23°	Full	4000 lbs	190 Gal.	25 Gal.	400
251	25'-4"	8'- 0"	14"	23°	25"/30"	3400 lbs	151 Gal.	X	370

261	26'-0"	8'-6"	16"	23°	30"	3900 lbs	200 Gal.	X	400
261B	28'-1"	8'- 6"	16"	23°	Full	4100 lbs	185 Gal.	X	450
263 WalkAround	28'-7"	9'-6"	19"	23°	Full	5000 lbs	240 Gal.	40 Gal.	550
286	28'-5"	9'- 10"	30"	13°	Full	8000 lbs	230 Gal.	20 Gal.	X
290 Sportsfish	28'-3"	10'-0"	23"	13°	Full	7500 lbs	300 Gal.	40 Gal.	600
295 Sportfish	31'-3"	10'- 0"	21"	13°	Full	6800 lbs	300 Gal.	40 Gal.	600

1995	Centerline Length	Beam	Hull Draft	Deadrise at Transom	Transom Height	Approx Weight	Fuel Capacity	Fresh Water Capacity	Max HP
17	17'-3"	7'-2"	9"	12°	20"	1250 lbs	35 Gal.	X	135
171 Flats	16'- 9"	7'- 3"	6"	12°	20"	850 lbs	35 Gal.	X	130
171 Angler	17'-0"	7'-0"	9"	12°	20"/25"	1250 lbs	45 Gal.	X	125
181 Flats	17'-10"	8'-0"	7"	12°	20"	995 lbs	50 Gal.	X	150
19	19'-0"	8'- 0"	9"	12°	25"	1900 lbs	60 Gal.	X	150
201	20'-4"	8'- 0"	11"	19°	25"	2150 lbs	100 Gal.	X	200
205 Dual	19'-10"	8'- 0"	13"	19°	25"	2000 lbs	86 Gal.	X	200
22	21'-10"	8'- 0"	13"	19°	25"	2200 lbs	110 Gal.	X	250
223 WalkAround	21'-9"	8'- 0"	13"	20°	Full	2700 lbs	98 Gal.	X	230
225 Dual	21'-10"	8'- 0"	13"	19°	25"	2400 lbs	110 Gal.	X	250
231	22'-8"	8'- 0"	13"	19°	25"/30"	2600 lbs	150 Gal.	X	280
232	22'-8"	8'- 0"	13"	19°	Full	2600 lbs	150 Gal.	X	250
236 Inboard	23'-0"	8'- 0"	24"	16°	Full	3800 lbs	80 Gal.	X	260
241	24'-4"	8'- 6"	16"	23°	25"/30"	3800 lbs	185 Gal.	X	400
243 WalkAround	23'-11"	8'-6"	14"	23°	Full	3000 lbs	125 Gal.	X	300
251	25'-4"	8'- 0"	14"	23°	25"/30"	3400 lbs	151 Gal.	X	370
261	26'-0"	8'-6"	16"	23°	30"	3900 lbs	200 Gal.	X	400
251	25'-4"	8'- 0"	14"	23°	25"/30"	3400 lbs	151 Gal.	X	370
261	26'-0"	8'-6"	16"	23°	30"	3900 lbs	200 Gal.	X	400
262	26'-2"	8'- 6"	16"	23°	Full	3800 lbs	150 Gal.	X	400
263 WalkAround	26'-2"	8'-6"	16"	23°	Full	4000 lbs	190 Gal.	25 Gal.	400
282	28'-1"	8'- 6"	16"	23°	Full	4100 lbs	185 Gal.	X	450
286	28'-5"	9'-10"	30"	13°	Full	8000 lbs	230 Gal.	20 Gal.	X
293 WalkAround	28'-7"	9'- 6"	19"	23°	Full	5000 lbs	240 Gal.	40 Gal.	550
295 Sportfish	31'-3"	10'-0"	21"	13°	Full	6800 lbs	300 Gal.	40 Gal.	600

1996	Centerline Length	Beam	Hull Draft	Deadrise at Transom	Transom Height	Approx Weight	Fuel Capacity	Fresh Water Capacity	Max HP
-------------	-------------------	------	------------	---------------------	----------------	---------------	---------------	----------------------	--------

17	17'-3"	7'-2"	9"	12°	20"/25"	1250 lbs	35 Gal.	X	135
171 Flats	16'- 9"	7'- 3"	6"	12°	20"	850 lbs	35 Gal.	X	130
181 Flats	17'-0"	8'-0"	7"	12°	20"	995 lbs	50 Gal.	X	150
19	19'-0"	8'-0"	9"	12°	25"	1900 lbs	60 Gal.	X	150
201	20'-4"	8'- 0"	11"	19°	25"	2150 lbs	100 Gal.	X	200
205 Dual	19'-10"	8'- 0"	13"	19°	25"	2000 lbs	86 Gal.	X	200
223 WalkAround	21'-9"	8'- 0"	13"	20°	25"	2700 lbs	98 Gal.	X	230
225 Dual	21'-10"	8'- 0"	13"	19°	25"	2400 lbs	110 Gal.	X	250
231	22'-8"	8'- 0"	13"	19°	25"/30"	2600 lbs	150 Gal.	X	280
232	22'-8"	8'- 0"	13"	19°	Full	2600 lbs	150 Gal.	X	250
243 WalkAround	23'-11"	8'- 6"	14"	23°	25"	3000 lbs	125 Gal.	X	300
251	25'-4"	8'- 0"	14"	23°	25"/30"	3400 lbs	151 Gal.	X	370
262	26'-2"	8'- 6"	16"	23°	25"/30"	3800 lbs	150 Gal.	X	400
263 WalkAround	26'-2"	8'- 6"	16"	23°	25"/30"	4000 lbs	190 Gal.	X	400
282	28'-1"	8'-6"	16"	23°	25"	4100 lbs	235/50 Gal.	X	450
293 WalkAround	28'-7"	9'- 6"	19"	23°	25"	5000 lbs	240 Gal.	40 Gal.	550
295 CC/Dual	31'-3"	10'-0"	21"	13°	25"	6800 lbs	300 Gal.	40 Gal.	600

1997	Centerline Length	Beam	Hull Draft	Deadrise at Transom	Transom Height	Approx Weight	Fuel Capacity	Fresh Water Capacity	Max HP
171	17'-3"	7'-2"	9"	12°	20"	1250 lbs	35 Gal.	X	135
171 LT	16'- 9"	7'- 3"	6"	12°	20"	850 lbs	35 Gal.	X	130
181 LT	17'-10"	8'-0"	7"	12°	20"	995 lbs	50 Gal.	X	150
191	19'-4"	8'-2"	12"	17°	25"	1900 lbs	70 Gal.	X	150
221	21'-10"	8'- 2"	13"	20°	25"	2600 lbs	120 Gal.	X	250
223 WalkAround	21'-9"	8'- 0"	13"	20°	25"	2700 lbs	98 Gal.	X	230
231	22'-8"	8'- 0"	13"	19°	25"/30"	2600 lbs	150 Gal.	X	280
232	22'-8"	8'- 0"	13"	19°	Full	2600 lbs	150 Gal.	X	250
243 WalkAround	24'-9"	8'- 6"	16"	23°	25"/30"	4000 lbs	130 Gal.	25 Gal.	400
252	24'-9"	8'- 6"	14"	23°	25"/30"	4000 lbs	200 Gal.	X	300
263 WalkAround	26'-2"	8'- 6"	16"	23°	25"/30"	4500 lbs	190 Gal.	25 Gal.	400
282	28'-1"	8'- 6"	16"	23°	25"	4500 lbs	235 Gal.	X	450
293 WalkAround	28'-7"	9'-6"	19"	23°	25"	5000 lbs	240 Gal.	40 Gal.	550
295 Dual	28'-3"	10'-0"	21"	13°	25"	6800 lbs	300 Gal.	40 Gal.	600
333 Attack	33'-9"	10'-6"	21"	24.5°	25"/30"	11,500 lbs	350 Gal.	40 Gal.	750

1998	Centerline Length	Beam	Hull Draft	Deadrise at Transom	Transom Height	Approx Weight	Fuel Capacity	Fresh Water Capacity	Max HP
171	17'-3"	7'-2"	9"	12°	20"	1250 lbs	35 Gal.	X	135
191	19'-4"	8'-2"	12"	17°	25"	1900 lbs	70 Gal.	X	150
221	21'-10"	8'- 2"	13"	20°	25"	2600 lbs	120 Gal.	X	250
223 WalkAround	21'-9"	8'- 2"	13"	20°	25"	2700 lbs	98 Gal.	X	230
232	22'-8"	8'- 0"	13"	19°	Full	3000 lbs	150 Gal.	X	250
252	24'-9"	8'-6"	14"	23°	25"/30"	4000 lbs	200 Gal.	opt.9 Gall0ns	300
253 WalkAround	24'-9"	8'- 6"	19"	23°	25"/30"	4000 lbs	130 Gal.	25 Gal.	400
282	28'-1"	8'- 6"	16"	23°	25"	4500 lbs	235 Gal.	opt.9 Gall0ns	450
293 WalkAround	28'-7"	9'- 6"	19"	23°	25"	6000 lbs	240 Gal.	40 Gal.	550
295 Dual	28'-3"	10'-0"	21"	13°	25"	7000 lbs	300 Gal.	40 Gal.	600
333 Attack	33'-9"	10'-6"	21"	24.5°	25"/30"	11,500 lbs	350 Gal.	40 Gal.	750
1999	Centerline Length	Beam	Hull Draft	Deadrise at Transom	Transom Height	Approx Weight	Fuel Capacity	Fresh Water Capacity	Max HP
171	17'-3"	7'-2"	9"	12°	20"	1250 lbs	35 Gal.	X	135
191	19'-4"	8'-2"	12"	17°	25"	1900 lbs	70 Gal.	X	150
192	19'-4"	8'- 6"	12"	16°	25"	1950 lbs	80 Gal.	X	150
195	19'-4"	8'- 6"	12"	16°	25"	2050 lbs	80 Gal.	opt.9 Gall0ns	150
BayShark 2100	21'-10"	8'- 4"	14"	17°	25"	2100 lbs	78 Gal.	X	225
221	21'-10"	8'-2"	14"	20°	25"	2600 lbs	120 Gal.	X	250
232	22'-9"	8'- 6"	14"	20°	25"/30"	3150 lbs	150 Gal.	opt.9 Gal.	300
233 WalkAround	22'-9"	8'- 6"	14"	20°	25"/30"	3400 lbs	145 Gal.	13 Gal.	300
252	24'-9"	8'- 6"	14"	23°	25"/30"	4000 lbs	190 Gal.	opt. 9 Gal.	400
253 WalkAround	24'-9"	8'-6 "	14"	23°	25"/30"	4000 lbs	130 Gal.	25 Gal.	400
282	28'-1"	8'-6"	16"	23°	25"	4500 lbs	235 Gal.	opt.9 Gal.	450
293 WalkAround	28'-7"	9'-6 "	19"	23°	25"	6100 lbs	240 Gal.	40 Gal.	450
333 Attack	33'-9"	10'-6"	21"	24.5°	25"/30"	11,500 lbs	350 Gal.	40 Gal.	750
2000	Centerline Length	Beam	Hull Draft	Deadrise at Transom	Transom Height	Approx Weight	Fuel Capacity	Fresh Water Capacity	Max HP
171	17'-3"	7'-2"	9"	12°	20"	1250 lbs	35 Gal.		135
191	19'-4"	8'-2"	12"	17°	25"	1900 lbs	70 Gal.		150
192	19'-4"	8'- 6"	12"	16°	25"	1950 lbs	80 Gal.		150
195	19'-4"	8'- 6"	12"	16°	25"	2050 lbs	80 Gal.	opt.9 Gall0ns	150
BayShark 2100	21'-10"	8'- 4"	14"	17°	25"	2100 lbs	78 Gal.		225

221	21'-10"	8'-2"	14"	20°	25"	2600 lbs	120 Gal.		250
232	22'-9"	8'- 6"	14"	20°	25"/30"	3150 lbs	150 Gal.	opt.9 Gal.	300
233 WalkAround	22'-9"	8'- 6"	14"	20°	25"/30"	3400 lbs	145 Gal.	13 Gal.	300
252	24'-9"	8'- 6"	14"	23°	25"/30"	4000 lbs	190 Gal.	opt. 9 Gal.	400
253 WalkAround	24'-9"	8'-6 "	14"	23°	25"/30"	4000 lbs	130 Gal.	25 Gal.	400
282	28'-1"	8'-6"	16"	23°	25"	4500 lbs	235 Gal.	opt.9 Gal.	450
2001	Centerline Length	Beam	Hull Draft	Deadrise at Transom	Transom Height	Approx Weight	Fuel Capacity	Fresh Water Capacity	Max HP
171	17'-3"	7'-2"	9"	12°	20"	1250 lbs	35 Gal.		135
191	19'-4"	8'-2"	12"	17°	25"	1900 lbs	70 Gal.		150
192	19'-4"	8'- 6"	12"	16°	25"	1950 lbs	80 Gal.		150
195	19'-4"	8'- 6"	12"	16°	25"	2050 lbs	80 Gal.	opt.9 Gall0ns	150
BayShark 2100	21'-10"	8'- 4"	14"	17°	25"	2100 lbs	78 Gal.		225
221	21'-10"	8'-2"	14"	20°	25"	2600 lbs	120 Gal.		250
232	22'-9"	8'- 6"	14"	20°	25"/30"	3150 lbs	150 Gal.	opt.9 Gal.	300
233 WalkAround	22'-9"	8'- 6"	14"	20°	25"/30"	3400 lbs	145 Gal.	13 Gal.	300
252	24'-9"	8'- 6"	14"	23°	25"/30"	4000 lbs	190 Gal.	opt. 9 Gal.	400
253 WalkAround	24'-9"	8'-6 "	14"	23°	25"/30"	4000 lbs	130 Gal.	25 Gal.	400
282	28'-1"	8'-6"	16"	23°	25"	4500 lbs	235 Gal.	opt.9 Gal.	450
293 WalkAround	28'-7"	9'-6 "	19"	23°	25"	6100 lbs	240 Gal.	40 Gal.	450
313	31'2"	10' -6"	23"	21°	35"	8,500 lbs	300 Gal.	40 Gal.	500
314	31'-2"	10'-6"	21"	21°	35"	7,500 lbs	300 Gal.	40 Gal.	500
2002	Centerline Length	Beam	Hull Draft	Deadrise at Transom	Transom Height	Approx Weight	Fuel Capacity	Fresh Water Capacity	Max HP
171	17'-3"	7'-2"	9"	12°	20"	1250 lbs	35 Gal.		135
191	19'-4"	8'-2"	12"	17°	25"	1900 lbs	70 Gal.		150
192	19'-4"	8'- 6"	12"	16°	25"	1950 lbs	80 Gal.		150
195	19'-4"	8'- 6"	12"	16°	25"	2050 lbs	80 Gal.	opt.9 Gal.	150
BayShark 2100	21'-10"	8'- 4"	14"	17°	25"	2100 lbs	78 Gal.		225
221	21'-10"	8'-2"	14"	20°	25"	2600 lbs	120 Gal.		250
232	22'-9"	8'- 6"	14"	20°	25"/30"	3150 lbs	150 Gal.	opt.9 Gal.	300
233 WalkAround	22'-9"	8'- 6"	14"	20°	25"/30"	3400 lbs	145 Gal.	13 Gal.	300
252	24'-9"	8'- 6"	14"	23°	25"/30"	4000 lbs	190 Gal.	opt. 9 Gal.	400
253 WalkAround	24'-9"	8'-6 "	14"	23°	25"/30"	4000 lbs	130 Gal.	25 Gal.	400
282	28'-1"	8'-6"	16"	23°	25"	4500 lbs	235 Gal.	opt.9 Gal.	450

293 WalkAround	28'-7"	9'-6 "	19"	23°	25"	6100 lbs	240 Gal.	40 Gal.	450
313	31'2"	10' -6"	23"	21°	35"	8,500 lbs	300 Gal.	40 Gal.	500
314	31'-2"	10'-6"	21"	21°	35"	7,500 lbs	300 Gal.	40 Gal.	500

2003	Centerline Length	Beam	Hull Draft	Deadrise at Transom	Transom Height	Approx Weight	Fuel Capacity	Fresh Water Capacity	Max HP
171	17'-3"	7'-2"	9"	12°	X	1250 lbs	40 Gal.	X	135
192	19'-4"	8'-6"	12"	16°	X	1950 lbs	80 Gal.	X	150
195	19'-4"	8'- 6"	12"	16°	X	2100 lbs	80 Gal.	X	150
201	20'-3"	8'-2"	12"	12°	X	2000 lbs	75 Gal.	X	200
221	21'-10"	8'-2"	14"	20°	X	2600 lbs	120 Gal.	X	250
232	22'-9"	8'- 6"	14"	20°	X	3150 lbs	150 Gal.	X	300
252	24'-9"	8'- 6"	14"	23°	X	4000 lbs	209 Gal.	X	400
253 WalkAround	24'-9"	8'-6 "	14"	23°	X	4000 lbs	130 Gal.	X	400
282	28'-1"	8'-6"	16"	23°	X	4500 lbs	235 Gal.	X	450
293 WalkAround	28'-7"	9'-6 "	19"	23°	X	6100 lbs	240 Gal.	X	450
313	31'3"	10'-6"	21"	21°	X	7,500 lbs	300 Gal.	X	500
314	31'-3"	10'-6"	21"	21°	X	7,500 lbs	300 Gal.	X	500

2004	Centerline Length	Beam	Hull Draft	Deadrise at Transom	Transom Height	Approx Weight	Fuel Capacity	Fresh Water Capacity	Max HP
171	17'-3"	7'-2"	9"	12°	X	1250 lbs	40 Gal.	X	135
192	19'-4"	8'-6"	12"	16°	X	1950 lbs	80 Gal.	X	150
195	19'-4"	8'- 6"	12"	16°	X	2100 lbs	80 Gal.	X	150
201	20'-3"	8'-2"	12"	12°	X	2000 lbs	75 Gal.	X	200
212 Center Cons	20'-5"	8'-6"	14"	18°	X	2400 lbs	100 Gal.	X	250
232	22'-9"	8'- 6"	14"	20°	X	3150 lbs	150 Gal.	X	300
252	24'-9"	8'- 6"	14"	23°	X	4000 lbs	209 Gal.	X	400
253 WalkAround	24'-9"	8'-6 "	14"	23°	X	4000 lbs	130 Gal.	X	400
314	31'-3"	10'-6"	21"	21°	X	7,500 lbs	300 Gal.	X	500
1901 Inshore	19'-4"	94"	12"	15°	X	1,575 lbs	47 Gal.	X	150
2101 Inshore	21'-4"	194"	12"	15°	X	1,790 lbs	60 Gal.	X	200

2005	Centerline Length	Beam	Hull Draft	Deadrise at Transom	Transom Height	Approx Weight	Fuel Capacity	Fresh Water Capacity	Max HP
171	17'-3"	7'-2"	9"	12°	X	1250 lbs	40 Gal.	X	135
192	19'-4"	8'-6"	12"	16°	X	1950 lbs	80 Gal.	X	150
195	19'-4"	8'- 6"	12"	16°	X	2100 lbs	80 Gal.	X	150

201	20'-3"	8'-2"	12"	12°	X	2000 lbs	75 Gal.	X	200
212 Center Cons	20'-5"	8'-6"	14"	18°	X	2400 lbs	100 Gal.	X	250
232	22'-9"	8'- 6"	14"	20°	X	3150 lbs	150 Gal.	X	300
252	24'-9"	8'- 6"	14"	23°	X	4000 lbs	209 Gal.	X	400
253 WalkAround	24'-9"	8'-6 "	14"	23°	X	4000 lbs	130 Gal.	X	400
314	31'-3"	10'-6"	21"	21°	X	7,500 lbs	300 Gal.	X	500
1901 Inshore	19'-4"	94"	12"	15°	X	1,575 lbs	47 Gal.	X	150
2101 Inshore	21'-4"	194"	12"	15°	X	1,790 lbs	60 Gal.	X	200

2006	Centerline Length	Beam	Hull Draft	Deadrise at Transom	Transom Height	Approx Weight	Fuel Capacity	Fresh Water Capacity	Max HP
284 CC	28'-4"	9'-10"	21"	21°	30"	6,000 lbs	235 gal.	X	600
264 CC	26'-0"	9'-2"	20"	21°	30"	4,500 lbs	194 gal.	X	450
234 CC	23'-4"	8'-6 "	14"	21°	30"	3,500 lbs	150 gal.	X	300
212 CC	21'-5"	8'-6"	14"	18°	25"	3,100 lbs	93 gal.	X	250
192 CC	19'-4"	8'- 6 "	12"	16°	25"	2,300 lbs	80 gal.	X	150
171 CC	17'-3"	7'-2"	9"	12°	20"	1,500 lbs	37 gal.	X	125
253 WA	27'-7"	8'-6"	14"	23°	30"	4,200 lbs	130 gal.	X	400
215 WA	21'-5"	8'-6"	16"	18°	25"	3,300 lbs	93 gal.	X	250
216 DC	21'-5"	8'- 6"	15"	18°	25"	3,200 lbs	93 gal.	X	250
195 DC	19'-4"	8'-6"	12"	16°	25"	2,600 lbs	80 gal.	X	150
181 Inshore	18'-0"	7'-6"	X	X	25"	990 lbs	35 gal.	X	90
191 Inshore	19'-3"	8'-3"	X	X	25"	1,320 lbs	47 gal.	X	175
211 Inshore	21'-9"	8'-3"	X	X	25"	1,400 lbs	60 gal.	X	225
241 Inshore	23'-11"	8'-6"	X	X	25"	1,400 lbs	96 gal.	X	275
1801 Inshore	17'-8"	7'-1"	X	X	25"	1,190 lbs	35 gal.	X	125
1901 Inshore	19'-1"	7'-8"	X	X	25"	1,575 lbs	47 gal.	X	150
2101 Inshore	21'-5"	7'-9"	X	X	25"	1,790 lbs	60 gal.	X	225
2201 Inshore	21'-5"	7'-9"	X	X	25"	1,890 lbs	60 gal.	X	225

2007	Centerline Length	Beam	Hull Draft	Deadrise at Transom	Transom Height	Approx Weight	Fuel Capacity	Fresh Water Capacity	Max HP
284 CC	28'-4"	9'-10"	21"	21°	30"	6,000 lbs	235 gal.	X	600
264 CC	26'-0"	9'-2"	20"	21°	30"	4,500 lbs	194 gal.	X	450
234 CC	23'-4"	8'-6"	18"	21°	30"	3,500 lbs	150 gal.	X	300
212 CC	21'-5"	8'-6"	14"	18°	25"	3,100 lbs	93 gal.	X	250
204 CC	20'-4"	8'-4"	12"	18°	25"	2,000 lbs	85 gal.	X	225

192 CC	19'-4"	8'- 6 "	12"	16°	25"	2,300 lbs	80 gal.	X	150
184 CC	18'-4"	8'-2"	12"	18°	25"	1,800 lbs	56 gal.	X	150
171 CC	17'-3"	7'-2"	9"	12°	20"	1,500 lbs	37 gal.	X	125
314 Cuddy	31'-3"	10'-6"	21"	21°	35"	7,500 lbs	300 gal.	X	600
284 WA	28'-4"	9'-10"	21"	X	30"	X	194 gal.	X	600
264 WA	26'-0"	9'-2"	21"	X	30"	6,500 lbs	174 gal.	X	450
215 WA	21'-5"	8'-6"	16"	18°	25"	3,300 lbs	93 gal.	X	250
216 DC	21'-5"	8'- 6"	16"	18°	25"	3,200 lbs	93 gal.	X	250
181 Inshore	17'-11"	7'-5"	15"	15°	25"	1,300 lbs	35 gal.	X	90
191 Inshore	19'-2"	8'-2"	16"	15°	25"	1,600 lbs	47 gal.	X	175
211 Inshore	21'-8"	8'-2"	16"	15°	25"	1,950 lbs	60 gal.	X	225
241 Inshore	23'-11"	8'-6"	16"	15°	25"	2,500 lbs	96 gal.	X	300
1801 Inshore	17'-7"	7'-1"	16"	15°	25"	1,400 lbs	35 gal.	X	125
1901 Inshore	18'-10"	7'-9"	16"	15°	25"	1,700 lbs	47 gal.	X	150
2101 Inshore	21'-4"	7'-9"	15"	15°	25"	2,000 lbs	60 gal.	X	225
2201 Inshore	21'-3"	7'-9"	16"	15°	25"	2,100 lbs	60 gal.	X	225